



<u>RANGE</u>	<u>LEAD LENGTH</u>
Min Temp(°C)
Max Temp.....(°C)

<u>SENSOR TYPE</u>	<u>STEM</u> $\leftarrow L \rightarrow$	<u>LEAD</u>
Pt100	3mm x	Curly Cord *
Other.....	4.7mm x	Straight Cord **
	6.3mm x	Stainless Steel Armour
	Other	* Curly Cord only comes in PVC
		** See Note

<u>TIP</u>	<u>LEAD MATERIAL</u>	<u>CONNECTOR</u>
Blunt	PVC	Plug
Point	Teflon	Tails
Chisel	Silicon	Other.....
Flat	Other.....	
Other.....		

** Note : Straight cord can come with stainless steel overbraid

SERVOTECH INSTRUMENTATION LTD
 6 WILLIAM PICKERING DRIVE
 ALBANY
 AUCKLAND, NEW ZEALAND
 PHONE: 64-9-415 8362
 FAX: 64-9-415 8361
 EMAIL: sales@servotech.co.nz
 WEBSITE: www.servotech.co.nz



Temperature management by design



TITLE: **T HANDLE RTD PROBE WITH LEAD**

DRAWN BY: _____ DATE: _____

GENERIC NO. **R17** A4

SCALE: NTS MATERIAL: _____

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN mm

THIS DRAWING IS EXCLUSIVE PROPERTY OF SERVOTECH INSTRUMENTATION LTD AND SHOULD NOT BE COPIED OR HANDED TO OTHER PARTIES WITHOUT PRIOR PERMISSION.