

NTC Thermometer

Features:

- CE-Mark approval
- Hand-Held lightweight design
- With pocket hook
- Highly accurate thermometer
- With MAX/DATA HOLD function
- With NTC temperature sensor probe
- Auto-power-off function
- With °C and °F function


Model: 706A

Applications:

- Greenhouse
- Office environment
- Labs
- Environment studies
- Weather monitoring
- Art galleries/Museums
- Department store
- Workshops

Specifications:

Display: 3½ digit liquid crystal display (LCD) with a maximum reading of 1999.

Low battery indication: The "  " is displayed when the battery voltage drops below the operating level.

Operating environment: 0°C to 50°C, at <70% relative humidity.

Storage temperature: -20°C to 60°C, 0 to 80% R.H. with battery removed from meter.

Accuracy: Stated accuracy at 23°C±2°C, <75% relative humidity.

Battery: 1.5V x 3pcs AAA size.

Dimensions: 160mm(H) x 48mm(W) x 24mm(D).

Weight: Approx. 77.7g (including battery).

Temperature:

Sensor: Thermistor NTC sensor

Range: -20°C to 150°C, -58°F to 482°F

Resolution: 0.1°/1° (auto)

Accuracy: ±1°C on -30°C to 250°C ranges

±2°C on -50°C to -30°C ranges

±2°F on -22°F to 482°F ranges

±4°F on -58°F to -22°F ranges

