



<u>RANGE</u>	<u>LEAD LENGTH</u>
Min Temp(°C)
Max Temp.....(°C)

<u>SENSOR TYPE</u>	<u>STEM</u> $\leftarrow L \rightarrow$	<u>LEAD</u>
J Type	3mm x	Curly Cord *
K Type	4.5mm x	Straight Cord **
Other.....	6mm x	
	Other	

* Curly Cord only comes in PVC
 ** See Note

<u>TIP</u>	<u>LEAD MATERIAL</u>	<u>CONNECTOR</u>
Blunt	PVC	Plug
Point	Teflon	Bare Tails
Chisel	Silicon	Other.....
Flat	Other.....	
Other.....		

** Note : Straight cord can come with stainless steel overbraid

SERVOTECH INSTRUMENTATION LTD
 6 WILLIAM PICKERING DRIVE
 ALBANY
 AUCKLAND, NEW ZEALAND
 PHONE: 64-9-415 8362
 FAX: 64-9-415 8361
 EMAIL: sales@servotech.co.nz
 WEBSITE: www.servotech.co.nz



Temperature management by design



TITLE: **T HANDLE THERMOCOUPLE PROBE WITH LEAD**

DRAWN BY: AC APPROVED BY: KV DATE: 7/3/13

GENERIC NO. **T17** A4

SCALE: NTS MATERIAL:

UNLESS OTHERWISE SPECIFIED,
 ALL DIMENSIONS ARE IN mm

THIS DRAWING IS EXCLUSIVE
 PROPERTY OF SERVOTECH
 INSTRUMENTATION LTD AND
 SHOULD NOT BE COPIED OR
 HANDED TO OTHER PARTIES
 WITHOUT PRIOR PERMISSION.