

<u>RANGE</u>		STEM	LEAD PROTECTION	
Min Temp:	(°C)	3.0mm x	 Stainless Overbraid	
IVIIII TEITIP	_(<)	4.5mm x	 SS Sprial Armour	
Max Temp:	(°C)	6.0mm x	 SS Retaining Wire	
Iviax Temp.	_()	Other:	 None	
SENSOR TYPE		HANDLE MATERIAL	<u>LEAD</u>	
Pt100		Stainless Steel	Length:	_
Pt1000		Plastic	2 Wire	
Duplex			3 Wire	
NTC:			4 Wire	
Other:			6 Wire (Duplex)	
TIP		LEAD MATERIAL	CONNECTOR	
Blunt		PVC	Bare Tails	
Point		Silicon	Plug:	
Flat		Teflon	Other:	
Chisel		Other:		
Other:				
	_			





HAND HELD RTD PROBE WITH FLEXIBLE LEAD

APPROVED BY: KV DATE: 21/12/2022

THIS DRAWING IS EXCLUSIVE PROPERTY GENERIC NUMBER: OF SERVOTECH INSTRUMENTATION LTD AND SHOULD NOT BE COPIED OR HANDED TO OTHER PARTIES WITHOUT PROPER PERMISSION.

R17P

MANUFACTURED IN NEW ZEALAND

Α4

SCALE: NTS