

BIMETALLIC DIAL THERMOMETERS

- All stainless steel construction IP65 case
- White dial face with large easy to read graduations
- Calibration Reset at rear of case
- Accuracy = 1% of full scale
- Safety Glass or Perspex Face available



SD 030

Model BA 5

**Bimetal Thermometer
5" Dial Every angle**

1/2" NPT Fixed Thread.

18 x Temperature Ranges
From - 50 to 50 Deg C
Up to 0 to 600 Deg C

Stem Length including thread
2.5", 4", 6", 9", 12", 15" & 18"

*Specify temperature range
and stem length with order*



Model BA 3

**Bimetal Thermometer
3" Dial Every angle**

1/2" NPT Fixed Thread

18 x Temperature Ranges
From - 50 to 50 Deg C
Up to 0 to 600 Deg C

Stem Length including thread
2.5", 4", 6", 9", 12", 15" & 18"

*Specify temperature range
and stem length with order*



SD 029

Model BL 3

**Bimetal Thermometer
3" Dial Back Connection**

1/2" NPT Fixed Thread

18 x Temperature Ranges
From - 50 to 50 Deg C
Up to 0 to 600 Deg C

Stem Length including thread
2.5", 4", 6", 9", 12", 15" & 18"

*Specify temperature range
and stem length with order*

For additional information and pricing.

SERVOTECH

6 William Pickering Drive, Albany, PO Box 302-561, N.H.M.C.,
Auckland 0751, New Zealand, Phone: 64-9-415 8362
Toll free: 0800 737 868, Fax: 64-9-415 8361,
Email: sales@servotech.co.nz, Website: www.servotech.co.nz