



<u>RANGE</u>	<u>LEAD LENGTH</u>
Min Temp .....(°C)	.....
Max Temp.....(°C)	.....

<u>SENSOR TYPE</u>	<u>STEM</u> $\leftarrow L \rightarrow$	<u>LEAD</u>
2K2	3mm x .....	Curly Cord *
3K3	4.7mm x .....	Straight Cord **
Other.....	6.3mm x .....	Stainless Steel Armour
	Other .....	* Curly Cord only comes in PVC
		** See Note

<u>TIP</u>	<u>LEAD MATERIAL</u>	<u>CONNECTOR</u>
Blunt	PVC	Plug
Point	Teflon	Tails
Chisel	Silicon	Other.....
Flat	Other.....	
Other.....		

\*\* Note : Straight cord can come with stainless steel overbraid

SERVOTECH INSTRUMENTATION LTD  
 6 WILLIAM PICKERING DRIVE  
 ALBANY  
 AUCKLAND, NEW ZEALAND  
 PHONE: 64-9-415 8362  
 FAX: 64-9-415 8361  
 EMAIL: sales@servotech.co.nz  
 WEBSITE: www.servotech.co.nz

 <i>Temperature management by design</i>		
TITLE: <b>T HANDLE NTC PROBE WITH LEAD</b>		
DRAWN BY: AC APPROVED BY: KV		DATE: 7/3/13
GENERIC NO. <b>N17T</b>		<b>A4</b>
SCALE: NTS		MATERIAL:

UNLESS OTHERWISE SPECIFIED,  
 ALL DIMENSIONS ARE IN mm

THIS DRAWING IS EXCLUSIVE  
 PROPERTY OF SERVOTECH  
 INSTRUMENTATION LTD AND  
 SHOULD NOT BE COPIED OR  
 HANDED TO OTHER PARTIES  
 WITHOUT PRIOR PERMISSION.