



RANGE		STEM		LEAD LENGTH	
Min Temp: _____ (°C)		3.0mm x _____			
		4.5mm x _____			
Max Temp: _____ (°C)		6.0mm x _____			
		9.5mm x _____			
		Other: _____			
SENSOR TYPE		LEAD MATERIAL		LEAD PROTECTION	
Type K	<input type="checkbox"/>	PVC	<input type="checkbox"/>	Stainless Overbraid	<input type="checkbox"/>
Type J	<input type="checkbox"/>	Glass Fibre	<input type="checkbox"/>	SS Spiral Armour	<input type="checkbox"/>
Type T	<input type="checkbox"/>	Teflon	<input type="checkbox"/>	None	<input type="checkbox"/>
Type N	<input type="checkbox"/>	Other: _____	<input type="checkbox"/>		
Other: _____	<input type="checkbox"/>				

SERVOTECH INSTRUMENTATION LTD 6 WILLIAM PICKERING DRIVE ALBANY AUCKLAND, NEW ZEALAND PHONE: 64-9-415 8362 FAX: 64-9-415 8361 EMAIL: sales@servotech.co.nz WEBSITE: www.servotech.co.nz	 	
	TITLE: THERMOCOUPLE PROBE WITH FLEXIBLE LEAD AND FERRULE	
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN mm	DRAWN BY: DV	APPROVED BY: KV
THIS DRAWING IS EXCLUSIVE PROPERTY OF SERVOTECH INSTRUMENTATION LTD AND SHOULD NOT BE COPIED OR HANDED TO OTHER PARTIES WITHOUT PROPER PERMISSION.	GENERIC NUMBER: T16	
	SCALE: NTS	MANUFACTURED IN NEW ZEALAND

A4