



RANGE

Min Temp: _____ (°C)

Max Temp: _____ (°C)

SENSOR TYPE		STEM	LEAD LENGTH
Type K	<input type="checkbox"/>	3.0mm x _____	_____
Type J	<input type="checkbox"/>	4.5mm x _____	
Type T	<input type="checkbox"/>	6.0mm x _____	
Type N	<input type="checkbox"/>	9.5mm x _____	
Other: _____	<input type="checkbox"/>	Other: _____	

COMPRESSION FITTING		LEAD MATERIAL	LEAD PROTECTION
1/4" BSP <input type="checkbox"/>	1/4" NPT <input type="checkbox"/>	PVC <input type="checkbox"/>	Stainless Overbraid <input type="checkbox"/>
1/2" BSP <input type="checkbox"/>	1/2" NPT <input type="checkbox"/>	Glass Fibre <input type="checkbox"/>	SS Spiral Armour <input type="checkbox"/>
		Teflon <input type="checkbox"/>	None <input type="checkbox"/>
Other: _____ <input type="checkbox"/>		Other: _____ <input type="checkbox"/>	

SERVOTECH INSTRUMENTATION LTD
 6 WILLIAM PICKERING DRIVE
 ALBANY
 AUCKLAND, NEW ZEALAND
 PHONE: 64-9-415 8362
 FAX: 64-9-415 8361
 EMAIL: sales@servotech.co.nz
 WEBSITE: www.servotech.co.nz

UNLESS OTHERWISE SPECIFIED,
 ALL DIMENSIONS ARE IN mm

THIS DRAWING IS EXCLUSIVE PROPERTY
 OF SERVOTECH INSTRUMENTATION LTD
 AND SHOULD NOT BE COPIED OR
 HANDED TO OTHER PARTIES WITHOUT
 PROPER PERMISSION.



THERMOCOUPLE PROBE WITH FLEXIBLE LEAD, FERRULE AND COMPRESSION FITTING

DRAWN BY: DV APPROVED BY: KV DATE: 21/12/2022

GENERIC NUMBER: **T16C** **A4**

SCALE: NTS MANUFACTURED IN NEW ZEALAND