



<u>RANGE</u>	<u>STEM</u>	<u>B-LENGTH</u>
Min Temp: _____ (°C)	3.0mm x _____ 4.5mm x _____	
Max Temp: _____ (°C)	6.0mm x _____ 9.5mm x _____ Other: _____	_____
<u>SENSOR TYPE</u>	<u>STEEL SLEEVE</u>	<u>LEAD PROTECTION</u>
Type K <input type="checkbox"/>	7.0mm x _____	A-Lead Spiral Armour <input type="checkbox"/>
Type T <input type="checkbox"/>	8.0mm x _____	B-Lead Spiral Armour <input type="checkbox"/>
Duplex <input type="checkbox"/>	Other: _____	
Other: _____ <input type="checkbox"/>		
<u>LEAD MATERIAL</u>	<u>A-LENGTH</u>	<u>TAILS</u>
PVC <input type="checkbox"/>		2 Wire <input type="checkbox"/>
Silicon <input type="checkbox"/>		4 Wire (Duplex) <input type="checkbox"/>
Teflon <input type="checkbox"/>	_____	
Other: _____ <input type="checkbox"/>		

Note: Other ferrule lengths available on request

SERVOTECH INSTRUMENTATION LTD 6 WILLIAM PICKERING DRIVE ALBANY AUCKLAND, NEW ZEALAND PHONE: 64-9-415 8362 FAX: 64-9-415 8361 EMAIL: sales@servotech.co.nz WEBSITE: www.servotech.co.nz			TITLE: AUTOCLAVE PROBE WITH SLEEVE, FLEXIBLE LEAD AND FERRULE	
			DRAWN BY: DV	APPROVED BY: KV
UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN mm	GENERIC NUMBER:		T16A	A4
	SCALE: NTS		MANUFACTURED IN NEW ZEALAND	